

**BESKRIVELSE**

Total tykkelse	EN 428	mm	2.00
Tykkelse slitesjikt	EN 429	mm	0.97
Vekt	EN 430	g/m <sup>2</sup>	2680
Bredde	EN 426	cm	200
Lengde	EN 426	lm	20





**KLASSIFISERING**

Norm	-	-	EN 649
Europaklasse	EN 685	-	34 - 43
Brannklassifisering	EN 13 501-1	klasse	B <sub>fl</sub> -s1
Elektrostatisk oppladning	EN 1815	kV	< 2
Friksjon, våt	DIN 51 130	klasse	R10

**TESTVERDIER**

Slitestyrke	EN 660.2	mm <sup>3</sup>	≤ 2.0
Slitasjegruppe	EN 649	gruppe	T
Type Binder Content	ISO 10582	type	
Dimensjonsstabilitet	EN 434	%	≤ 0.40
Inntrykksfasthet	EN 433	mm	≤ 0.10
Målresultat	-	mm	~ 0.03
Rullende stolhjul (typen W)	EN 425	-	P3
Varmemotstand	EN 12 524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Kjemikaliebestandighet	EN 423	-	OK
Antibakterie og muggbehandlet	-	-	Sanosol®
Overflatebehandling	-	-	Protecsol®

**CE MARKING**

	EN 14041	-	  
		-	