

**BESKRIVELSE**

Total tykkelse	EN 428	mm	3.20
Tykkelse slitesjikt	EN 429	mm	1.16
Vekt	EN 430	g/m <sup>2</sup>	3080
Bredde	EN 426	cm	200
Lengde	EN 426	lm	20





**KLASSIFISERING**

Norm	-	-	EN 651
Europaklasse	EN 685	-	34 - 43
K klasse	-	klasse	
Brannklassifisering	EN 13501-1	klasse	B <sub>fl</sub> -s1
Elektrostatisk oppladning	EN 1815	kV	< 2
Friskjon, tørr	BS 7976	PTV	
Overflate ruhet	-	µm	Rz ≥ 20
Friskjon, våt	DIN 51 130	klasse	R11

**TESTVERDIER**

Slitestyrke	EN 660.2	mm <sup>3</sup>	≤ 2
Slitasjegruppe	EN 651	gruppe	
Dimensjonsstabilitet	EN 434	%	≤ 0.40
Inntrykksfasthet	EN 433	mm	≤ 0.20
Rullende stolhjul (typen W)	EN 425	-	P3
Trinnlydsdemping	EN ISO 717-2	dB	16
Varmemotstand	EN 12524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Kjemikaliebestandighet	EN 423	-	OK
Antibakterie og muggbehandlet	-	-	Sanosol®
Overflatebehandling	-	-	SparClean®

**CE MARKING**

	EN 14041	-	  
		-	